



**Cable ID: TP-6A-F/7 1-1**


Date / Time: 01/07/2019 11:05:45 AM  
**Headroom 3.4 dB (NEXT 36-45)**  
**Test Limit: ISO Patch Cord Cat6A 2.0m**  
 Cable Type: Cat 6A F/UTP  
 NVP: 74.0%

Operator: PGU  
 Software Version: 2.7800  
 Limits Version: 1.9500  
 Calibration Date:  
 Main (Tester): 08/16/2017  
 Remote (Tester): 08/16/2017


**Test Summary: PASS**

Model: DTX-1800  
 Main S/N: 8788118  
 Remote S/N: 8788119  
 Main Adapter: DTX-PC6A/MN ISO/IEC  
 Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 78]	7
Prop. Delay (ns)	[Pair 12]	11
Delay Skew (ns)	[Pair 12]	1
Resistance (ohms)	[Pair 45]	0.9



Wire Map (T568B)  
**PASS**



Worst Case Margin Worst Case Value

<b>PASS</b>	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
<b>NEXT (dB)</b>	3.4		3.9	
Freq. (MHz)	309.0		500.0	
Limit (dB)	36.4		31.0	

<b>PASS</b>	MAIN	SR	MAIN	SR
Worst Pair	36		78	
<b>RL (dB)</b>	4.6		6.3	
Freq. (MHz)	19.9		485.0	
Limit (dB)	23.7		9.7	

