



Cable ID: TP-6A-U/7 1-1


Date / Time: 01/07/2019 10:00:43 AM
Headroom 2.1 dB (NEXT 36-45)
Test Limit: ISO Patch Cord Cat6A 2.0m
 Cable Type: Cat 6A U/UTP
 NVP: 68.2%

Operator: PGU
 Software Version: 2.7800
 Limits Version: 1.9500
 Calibration Date:
 Main (Tester): 08/16/2017
 Remote (Tester): 08/16/2017


Test Summary: PASS

Model: DTX-1800
 Main S/N: 8788118
 Remote S/N: 8788119
 Main Adapter: DTX-PC6A/MN ISO/IEC
 Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 36]	7
Prop. Delay (ns)	[Pair 12]	11
Delay Skew (ns)	[Pair 12]	1
Resistance (ohms)	[Pair 12]	1.4



Wire Map (T568B)
PASS



	Worst Case Margin		Worst Case Value	
PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.1		2.1	
Freq. (MHz)	480.0		480.0	
Limit (dB)	31.5		31.5	

	Worst Case Margin		Worst Case Value	
PASS	MAIN	SR	MAIN	SR
Worst Pair	12		12	
RL (dB)	4.6		4.6	
Freq. (MHz)	364.0		367.0	
Limit (dB)	11.6		11.5	

